

MARINE GENERATOR SPECIFICATIONS



KOHLER[®]
IN POWER. SINCE 1920.

	Generator Model	kW*	Hz	Cylinder	RPM	Phase	Voltage		Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused	Weight (Wet) kg (lb)
GASOLINE	5EKD	5	60	2	3600	1	120	41.7	H – 773 (30.4) x 500 (19.7) x 467 (18.4) U – 691 (27.2) x 466 (18.4) x 445 (17.5)	H – 132 (290) U – 120 (265)	
							120 / 240	20.8			
							115 / 230	17.4			
	4EFKD	4	50		3000		230	17.4			
							240	16.7			
							240	62.5			
	7.5EKD	7.5	60	3600	2	1	120	31.3	H – 773 (30.4) x 500 (19.7) x 467 (18.4) U – 691 (27.2) x 466 (18.4) x 445 (17.5)	H – 132 (290) U – 120 (265)	
							120 / 240	26.1			
							115 / 230	26.1			
	6EFKD	6	50	3000			230	25			
							240	25			
							240	25			
10EKD	10	60	2	3600	1	120	83.3	H – 800 (31.5) x 500 (19.7) x 467 (18.4) U – 717 (28.2) x 466 (18.4) x 445 (17.5)	H – 147 (325) U – 136 (300)		
						120 / 240	41.7				
						115 / 230	34.8				
8EFKD	8	50		3000		230	34.8				
						240	33.3				
						240	33.3				

	Generator Model	kW*	Hz	Cylinder	RPM	Phase	Voltage		Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused	Weight (Wet) kg (lb)	
DIESEL	6EKOD	6	60	3	1800	1	120	50	H – 780 (30.7) x 528 (20.8) x 559 (22) U – 743 (29.3) x 448 (17.6) x 536 (21.1)	H – 222 (489) U – 185 (407)		
							120 / 240	50 / 25				
							115 / 230	43.4 / 21.7				
	5EFKOD	5	50		1500		230	21.7				
							240	20.8				
							240	20.8				
	9EKOZD	8.5	60	3	1800	1	120	70.8	H – 865 (34.1) x 528 (20.8) x 559 (22) U – 827 (32.6) x 448 (17.6) x 536 (21.1)	H – 249 (548) U – 211 (465)		
							120 / 240	70.8 / 35.4				
							115 / 230	60.8 / 30.4				
	7EFKOZD	7	50		1500		230	30.4				
							240	29.2				
							240	29.2				
	11EKOZD	11	60	4	1800	1	120	91.7	H – 960 (37.8) x 528 (20.8) x 559 (22) U – 922 (36.3) x 448 (17.6) x 536 (21.1)	H – 279 (616) U – 241 (532)		
							120 / 240	91.7 / 45.8				
							115 / 230	78.3 / 39.1				
	9EFKOZD	9	50		1500		230	39.1				
							240	37.5				
							240	37.5				
	11EKOZD	11	60	4	1800	3	220 / 380	20.9	H – 960 (37.8) x 528 (20.8) x 559 (22) U – 922 (36.3) x 448 (17.6) x 536 (21.1)	H – 406 (896) U – 376 (830)		
							240 / 416	19.1				
							120 / 240	33.1				
	9EFKOZD	9	50		1500		127 / 220	36.1				
							230 / 400	16.2				
							230 / 400	16.2				
14EKOZD	14	60	3	1800	1	120	117	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9) U – 984 (38.8) x 580 (22.8) x 695 (27.4)	H – 395 (870) U – 376 (830)			
						120 / 240	59					
						230	53					
12EFKOZD	12	50		1500		240	40					
						240	40					
						240	40					
14EKOZD	14	60	3	1800	3	120 / 208	49	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9) U – 984 (38.8) x 580 (22.8) x 695 (27.4)	H – 406 (896) U – 376 (830)			
						120 / 240	43					
						1	120 / 240			59		
							3			127 / 220	46	
										139 / 240	43	
						277 / 480				22		
12EFKOZD	12	50		1500	3	3	110 / 190			46		
							115 / 230			38		
							1			115 / 230	53	
										3	120 / 208	42
											230 / 400	22
							240 / 416				21	
220 / 380	23											
16EKOZD	16	60	3	1800	1	120	134	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9) U – 1003 (39.5) x 580 (22.8) x 695 (27.4)	H – 46 (896) U – 376 (830)			
						120 / 240	67					
						230	59					
13.5EFKOZD	14	50		1500		240	40					
						240	40					
						240	40					
16EKOZD	16	60	3	1800	3	120 / 208	56	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9) U – 1003 (39.5) x 580 (22.8) x 695 (27.4)	H – 406 (896) U – 376 (830)			
						120 / 240	49					
						1	120 / 240			67		
							3			127 / 220	53	
										139 / 240	49	
						277 / 480				25		
13.5EFKOZD	13.5	50		1500	3	3	110 / 190			52		
							115 / 230			43		
							1			115 / 230	59	
										3	120 / 208	47
											230 / 400	25
							240 / 416				24	
220 / 380	26											

	Generator Model	kW*	Hz	Cylinder	RPM	Phase	Voltage	Amps	Length x Width x Height mm (in)	Weight (Wet) kg (lb)
									H – Housed / U – Unhoused	
DIESEL	21EKOZD	21	60	4	1800	1	120	175	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9) U – 1121 (44.1) x 577.5 (22.7) x 694 (27.3)	H – 480 (1059) U – 440 (970)
	18EFKOZD	18	50				1500	120 / 240		
	21EKOZD	21	60	4	1800	3	240	61	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9) U – 1121 (44.1) x 577.5 (22.7) x 694 (27.3)	H – 480 (1059) U – 440 (970)
							120 / 208	73		
							120 / 240	64		
							120 / 240	80		
							127 / 220	69		
							139 / 240	64		
	17EFKOZD	17	50	4	1500	3	277 / 480	32	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9) U – 1121 (44.1) x 577.5 (22.7) x 694 (27.3)	H – 480 (1059) U – 440 (970)
							110 / 190	65		
							115 / 230	54		
							115 / 230	70		
							120 / 208	58		
							230 / 400	31		
	24EKOZD	24	60	4	1800	1	240 / 416	29	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9) U – 1138 (44.8) x 577.5 (22.7) x 694 (27.3)	H – 489 (1078) U – 449 (990)
							220 / 380	33		
							120	200		
							120 / 240	100		
							230	90		
							240	78		
	20.5EFOZD	20.5	50	4	1500	3	120 / 208	84	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9) U – 1138 (44.8) x 577.5 (22.7) x 694 (27.3)	H – 489 (1078) U – 449 (990)
							120 / 240	73		
							120 / 240	92		
							127 / 220	79		
							139 / 240	73		
							277 / 480	37		
	20.5EFOZD	20.5	50	4	1500	3	110 / 190	78	H – 1295 (51) x 635 (25) x 810 (31.9) U – 1188 (46.8) x 635 (25) x 767 (30.2)	H – 628 (1385) U – 583 (1285)
							115 / 230	65		
115 / 230							85			
120 / 208							72			
230 / 400							37			
240 / 416							36			
28EOZD	28	60	4	1800	1	220 / 380	39	H – 1295 (51) x 635 (25) x 810 (31.9) U – 1188 (46.8) x 635 (25) x 767 (30.2)	H – 628 (1385) U – 583 (1285)	
						120 / 240	117			
25EFOZD	25	50	4	1500	1	115 / 230	109	H – 1295 (51) x 635 (25) x 810 (31.9) U – 1188 (46.8) x 635 (25) x 767 (30.2)	H – 628 (1385) U – 583 (1285)	
28EOZD	28	60	4	1800	3	230	109			
						240	104			
						120 / 208	97			
						120 / 240	84			
						120 / 240	117			
						127 / 220	92			
25EFOZD	25	50	4	1500	3	139 / 240	84	H – 1295 (51) x 635 (25) x 810 (31.9) U – 1188 (46.8) x 635 (25) x 767 (30.2)	H – 633 (1395) U – 587 (1295)	
						277 / 480	42			
						110 / 190	95			
						115 / 230	78			
						115 / 230	109			
						120 / 208	87			
32EOZD	32	60	4	1800	1	230 / 400	45	H – 1295 (51) x 635 (25) x 810 (31.9) U – 1188 (46.8) x 635 (25) x 767 (30.2)	H – 628 (1385) U – 583 (1285)	
						240 / 416	43			
28EFOZD	28	50	4	1500	1	220 / 380	47	H – 1295 (51) x 635 (25) x 810 (31.9) U – 1188 (46.8) x 635 (25) x 767 (30.2)	H – 628 (1385) U – 583 (1285)	
32EOZD	32	60	4	1800	3	120 / 240	133			
						115 / 230	122			
						230	122			
						240	117			
						120 / 208	111			
						120 / 240	96			
28EFOZD	28	50	4	1500	3	120 / 240	133	H – 1295 (51) x 635 (25) x 810 (31.9) U – 1188 (46.8) x 635 (25) x 767 (30.2)	H – 633 (1395) U – 587 (1295)	
						127 / 220	105			
						139 / 240	96			
						277 / 480	48			
						110 / 190	106			
						115 / 230	88			
28EFOZD	28	50	4	1500	3	115 / 230	117	H – 1295 (51) x 635 (25) x 810 (31.9) U – 1188 (46.8) x 635 (25) x 767 (30.2)	H – 633 (1395) U – 587 (1295)	
						120 / 208	97			
						230 / 400	51			
						240 / 416	49			
						220 / 380	53			

*kW rating varies by voltage. Consult the generator spec sheet for more detail.

Generator Model	kW*	Hz	Cylinder	RPM	Phase	Voltage	Amps	Length x Width x Height mm (in)		Weight (Wet) kg (lb)
								H - Housed / U - Unhoused / R - Radiator		
40EOZDJ	40	60	4	1800	3	120 / 208	139	H - 1633 (64.3) x 767 (30.2) x 1015 (39.9) U - 1524 (60) x 722 (28.4) x 960 (37.8) R - 1858 (73.2) x 827 (32.6) x 1265 (49.8)	H - 1025 (2260) U - 935 (2060) R - 957 (2110)*	
					1	120 / 240	120			
					3	120 / 240	150			
3	127 / 220	131								
3	139 / 240	120								
3	277 / 480	60								
33EFOZDJ	33	50	4	1500	3	110 / 190	125	H - 1633 (64.3) x 767 (30.2) x 1015 (39.9) U - 1524 (60) x 722 (28.4) x 960 (37.8) R - 1858 (73.2) x 827 (32.6) x 1265 (49.8)	H - 1025 (2260) U - 935 (2060) R - 957 (2110)*	
					1	110 / 220	108			
					3	115 / 230	143			
3	220 / 380	63								
3	230 / 400	60								
3	240 / 416	57								
40EFOZDJ	40	50	4	1500	3	110 / 190	152	H - 1633 (64.3) x 767 (30.2) x 1015 (39.9) U - 1549 (60.9) x 738 (29) x 961 (37.8) R - 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H - 1080 (2380) U - 971 (2140) R - 993 (2190)*	
					1	110 / 220	131			
					3	115 / 230	174			
3	220 / 380	76								
3	230 / 400	72								
3	240 / 416	69								
50EFOZDJ	50	50	4	1500	3	110 / 190	190	H - 1690 (66.5) x 767 (30.2) x 1015 (39.9) U - 1606 (63.2) x 738 (29) x 961 (37.8) R - 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H - 1114 (2456) U - 1005 (2216) R - 1028 (2266)*	
					1	110 / 220	164			
					3	115 / 230	196			
3	220 / 380	95								
3	230 / 400	90								
3	240 / 416	87								
55EOZDJ	55	60	4	1800	3	120 / 208	191	H - 1633 (64.3) x 767 (30.2) x 1015 (39.9) U - 1549 (60.9) x 738 (29) x 961 (37.8) R - 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H - 1090 (2404) U - 982 (2164) R - 1004 (2214)*	
					1	120 / 240	165			
					3	120 / 240	221			
3	127 / 220	180								
3	139 / 240	165								
3	277 / 480	83								
45EFOZDJ	45	50	4	1500	3	110 / 190	171	H - 1633 (64.3) x 767 (30.2) x 1015 (39.9) U - 1549 (60.9) x 738 (29) x 961 (37.8) R - 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H - 1090 (2404) U - 982 (2164) R - 1004 (2214)*	
					1	110 / 220	148			
					3	115 / 230	196			
3	220 / 380	86								
3	230 / 400	79								
3	240 / 416	71								
65EOZDJ	65	60	4	1800	3	120 / 208	226	H - 1690 (66.5) x 767 (30.2) x 1015 (39.9) U - 1606 (63.2) x 738 (29) x 961 (37.8) R - 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H - 1125 (2480) U - 1016 (2240) R - 1039 (2290)*	
					1	120 / 240	195			
					3	120 / 240	221			
3	127 / 220	213								
3	139 / 240	195								
3	277 / 480	98								
55EFOZDJ	55	50	4	1500	3	110 / 190	209	H - 1690 (66.5) x 767 (30.2) x 1015 (39.9) U - 1606 (63.2) x 738 (29) x 961 (37.8) R - 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H - 1125 (2480) U - 1016 (2240) R - 1039 (2290)*	
					1	110 / 220	181			
					3	115 / 230	217			
3	220 / 380	105								
3	230 / 400	95								
3	240 / 416	89								
80EOZDJ	80	60	4	1800	3	120 / 208	278	H - 1754 (69) x 831 (32.7) x 1032 (40.6) U - 1657 (65.2) x 753 (29.6) x 999 (39.3) R - 1992 (78.4) x 890 (35) x 1277 (50.2)	H - 1270 (2800) U - 1148 (2530) R - 1179 (2600)*	
					1	120 / 240	241			
					3	120 / 240	262			
3	127 / 220	262								
3	139 / 240	241								
3	277 / 480	120								
70EFOZDJ	70	50	4	1500	3	110 / 190	266	H - 1754 (69) x 831 (32.7) x 1032 (40.6) U - 1657 (65.2) x 753 (29.6) x 999 (39.3) R - 1992 (78.4) x 890 (35) x 1277 (50.2)	H - 1270 (2800) U - 1148 (2530) R - 1179 (2600)*	
					1	110 / 220	230			
					3	115 / 230	333			
3	220 / 380	133								
3	230 / 400	126								
3	240 / 416	121								
99EOZDJ	99	60	4	1800	3	120 / 208	343	H - 1829 (72) x 831 (32.7) x 1032 (40.6) U - 1732 (68.2) x 753 (29.6) x 999 (39.3) R - 2067 (81.3) x 890 (35) x 1277 (50.2)	H - 1356 (2990) U - 1243 (2740) R - 1275 (2810)*	
					1	120 / 240	298			
					3	120 / 240	325			
3	127 / 220	325								
3	139 / 240	298								
3	277 / 480	149								
80EFOZDJ	80	50	4	1500	3	110 / 190	304	H - 1829 (72) x 831 (32.7) x 1032 (40.6) U - 1732 (68.2) x 753 (29.6) x 999 (39.3) R - 2067 (81.3) x 890 (35) x 1277 (50.2)	H - 1356 (2990) U - 1243 (2740) R - 1275 (2810)*	
					1	110 / 220	262			
					3	115 / 230	328			
3	220 / 380	152								
3	230 / 400	144								
3	240 / 416	139								
125EOZDJ	125	60	6	1800	3	120 / 208	434	H - 2205 (86.8) x 971 (38.2) x 1065 (41.9) U - 2068 (81.4) x 893 (35.2) x 1003 (39.5) R - 2466 (97.1) x 1129 (44.5) x 1275 (50.2)	H - 1683 (3710) U - 1515 (3340) R - 1578 (3478)	
					1	120 / 240	376			
					3	120 / 240	410			
3	127 / 220	410								
3	139 / 240	376								
3	277 / 480	188								
100EFOZDJ	100	50	6	1500	3	110 / 190	380	H - 2205 (86.8) x 971 (38.2) x 1065 (41.9) U - 2068 (81.4) x 893 (35.2) x 1003 (39.5) R - 2466 (97.1) x 1129 (44.5) x 1275 (50.2)	H - 1683 (3710) U - 1515 (3340) R - 1578 (3478)	
					1	110 / 220	347			
					3	115 / 230	328			
3	220 / 380	190								
3	230 / 400	180								
3	240 / 416	173								
150EOZDJ	150	60	6	1800	3	120 / 208	520	H - 2205 (86.8) x 971 (38.2) x 1065 (41.9) U - 2091 (82.3) x 893 (35.2) x 1003 (39.5) R - 2498 (98) x 1129 (44.5) x 1275 (50.2)	H - 1719 (3789) U - 1551 (3419) R - 1613 (3557)	
					1	120 / 240	451			
					3	120 / 240	492			
3	127 / 220	492								
3	139 / 240	451								
3	277 / 480	226								
125EFOZDJ	125	50	6	1500	3	110 / 190	474	H - 2205 (86.8) x 971 (38.2) x 1065 (41.9) U - 2091 (82.3) x 893 (35.2) x 1003 (39.5) R - 2498 (98) x 1129 (44.5) x 1275 (50.2)	H - 1719 (3789) U - 1551 (3419) R - 1613 (3557)	
					1	110 / 220	433			
					3	115 / 230	409			
3	220 / 380	237								
3	230 / 400	225								
3	240 / 416	217								
200EOZDJ	200	60	6	1800	3	120 / 208	694	H - 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U - 2490 (98) x 970 (38.2) x 1086 (42.8)	H - 2147 (4733) U - 2067 (4558)	
					1	120 / 240	601			
					3	120 / 240	656			
3	127 / 220	656								
3	139 / 240	601								
3	277 / 480	301								
175EFOZDJ	175	50	6	1500	3	110 / 190	665	H - 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U - 2490 (98) x 970 (38.2) x 1086 (42.8)	H - 2147 (4733) U - 2067 (4558)	
					1	110 / 220	574			
					3	115 / 230	607			
3	220 / 380	332								
3	230 / 400	316								
3	240 / 416	304								

DIESEL

*kW rating varies by voltage. Consult the generator spec sheet for more detail.